

Smart Inverter Series

Features :

Pure sine wave output

Optional MPPT/PWM solar charge controller 60A

MPPT Efficiency max 98%

DC Start & Automatic Self-Diagnostic Function

High Efficiency Design & "Power Saving Mode" to Conserve Energy

Auto restart when Ac in recovering

Smart battery charger design for optimized battery performance

Selectable charging current based on applications

AC input/DC input/Solar input optional priority

Auto Restart Voltage



Model	1KW MPPT
Input Voltage(AC)	220VAC(Standard)
Nominal Voltage	154-264VAC±3V (Normal Mode) 185-264VAC±3V (UPS Mode)
Input Voltage(DC)	154-264VAC±3V (Normal Mode) 185-264VAC±3V (UPS Mode)
Frequency	50/60Hz±5%
Rated Power	1000W
AC Type Output Voltage	Output voltage under mains power same as the input voltage
AC Type Output Frequency	Frequency under mains power same as the input voltage
Output Voltage(AC)	220VAC±10% (110VAC±10%)
Output Frequency (AC)	50HZ/60HZ±1%
Waveform	Pure Sine Wave
Battery Type	External lead acid battery or water battery, or lithium battery
Battery Voltage	12VDC/24VDC
Battery Charging Voltage	13.7VDC/27.4VDC
Maximum PV array power	12V: 800W 24V: 1600W
PV Input Voltage Range (MPPT)	12V: MPPT 15V-150VDC
Maximum photovoltaic display open circuit voltage	12V: MPPT 150VDC
Best Vmp Working Range	12V: MPPT 15-105VDC
Maximum solar charging current	60A
Maximum AC charging current	25A / 13A
Transfer Time	≤10ms (UPS Mode) /≤20ms (INV Mode)
Load peak ratio	(MAX)3:1
Standby power consumption (W)	Transformer 12V : 8W
Protection	Under the main power: input overcurrent fuse
	Under inverter: overload protection, short circuit protection, low voltage protection, (with battery anti-reverse connection, board).
LCD indicator status	Color segment code screen with LED display
	AC input voltage, AC input frequency, PV voltage, PV current, Output Voltage, Output Frequency, Battery voltage, Load current etc.
	LED display of mains power, charging status, inverter status, and fault status
Audible alarm	The buzzer distinguishes between long and short tones based on different fault codes and alarm sounds
Working Temperature	0°C~40°C
Storage Temperature	-15°C~45°C
Humidity	-10°C~90°C
Acoustic Noise(db)	<45dB
Dimension (L*W*H)mm	465*310*135MM
Weight(kg)	12.09KG